

Specification

Stock No	350725
Туре	REACH
Make	LINDE
Model	R16S 115
Year	2009
Euromast	3F660
Hours	10004
Capacity	1600 kg
Lift height	6600
Values	
Quality Rating	0
Mechanical	
Character.	
Operating mode (Characteristic)	Seated
Weights	
Service weight (Total weight)	3230 kg
Wheels	
Tyres type	Polyurethane
Tyres type	Polyurethane
Tyres type Dimensions	
Tyres type Dimensions Free lift (h2)	1920 mm
Tyres type Dimensions Free lift (h2) Lift height (h3)	
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin)	1920 mm 6600 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6)	1920 mm 6600 mm 7600 mm 2110 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1500 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1500 mm 1250 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1500 mm 1250 mm 1250 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1500 mm 1250 mm 1250 mm 1000 mm DIN 15173 / 24
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1500 mm 1250 mm 1250 mm 1000 mm DIN 15173 / 2 <i>A</i> 830 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1250 mm 1250 mm 1250 mm 1000 mm 1250 mm 1000 mm 922 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4) Reach travel (l4)	1920 mm 6600 mm 7600 mm 2110 mm 2500 mm 1500 mm 1250 mm 1000 mm 1000 mm DIN 15173 / 24 830 mm 922 mm 530 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (11) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4) Reach travel (l4) Ground clearance, mast (m1)	1920 mm 6600 mm 7600 mm
Tyres type Dimensions Free lift (h2) Lift height (h3) Extended height (h4) Height of overhead guard (cabin) (h6) Height of reach legs (h8) Overall length (l1) Length to fork face (l2) Overall width (b1/b2) Forks length (l) Forks length (l) Fork carriage (class) Fork carriage width (b3) Width between legs (b4) Reach travel (l4)	1920 mm 6600 mm 7600 mm 2110 mm 310 mm 2500 mm 1500 mm 1250 mm 1000 mm DIN 15173 / 2 <i>A</i> 830 mm 922 mm 530 mm 75 mm

Performance Service brake

electromagnetic

Drive	
Battery weight	986 kg
Drive motor (60 min rating)	6.5 kW
Lift motor (15% rating)	10 kW
Battery class	British Standard
Battery voltage/capacity	48V / 560Ah V/Ah
Battery (Acc. to DIN)	GNB MARATHON CLASSIC

Attachment

Attachments (Has attachment) Attachment type (Attachment type)	Sideshift and Forks. Sideshifts
Engine Engine type (Engine type)	electric
Opinion	
Location	
Extras	

Extras	SS
Extras Hyds	3rd & 4th
To carriage	1

2009

Visual

Battery Battery Year (Battery Year of Manufacture)



Appearance: Good Appearance for age. Seat worn, arm rest cushion ripped

Mechanical Status: Good operating condition.

More: Click here for more photos









Phone: Email: Website: +44(0) 1784 818181 sales@phl.co.uk https://www.phl.co.uk